



Sandblast Slags
Foundry Sands
Empire Blast Equipment
Bullard Safety Equipment
Sandblast Hose & Nozzles
Walnut Shells & Corn Cob Grit
Waterjet & Sandblast Garnet
Schmidt Blast Equipment
Silica Free Abrasives
Steel Shot & Grit
Aluminum Oxide
Glass Beads

#420 SILICA SAND

TYPICAL SCREEN ANALYSIS

U.S. SIEVE	% RETAINED
30 Mesh	.30%
40 Mesh	15.30%
50 Mesh	37.90%
70 Mesh	29.00%
100 Mesh	12.10%
140 Mesh	4.30%
200 Mesh	1.00%
270 Mesh	.10%
PAN	----
AFS	49

TYPICAL CHEMICAL ANALYSIS

Silicon Dioxide (SiO ₂)	99.65%
Iron Oxide (Fe ₂ O ₃)	.02%
Aluminum Oxide (Al ₂ O ₃)	.07%
Calcium Oxide (CaO)	.01%
Titanium Dioxide (TiO ₂)	.01%
Magnesium Oxide (MgO)	.01%
Potassium Oxide (K ₂ O)	<.01%
Sodium Oxide (Na ₂ O)	.01%
Loss on Ignition	.07%
Acid Demand Value (ADV)	1.0
Clay Content	.10%
Colour:	White
Grain Shape:	Rounded
Specific Gravity:	2.65
Bulk Density/Loose	92-95 lbs./cu.ft.

WARNING: This product contains free silica. Repeated inhalation of respirable free silica may cause delayed lung injury known as silicosis. Follow current OSHA Safety and Health Standards for Crystalline Silica (Quartz). All products are sold without warranty expressed or implied and seller specifically does not warrant that these products are suitable for a particular purpose or purposes or are merchantable. Buyer agrees it does not rely on seller's skill or judgment to select or furnish these products. Buyer shall make its own tests to determine the suitability of such product for its purposes. July 2019

Tel: (905) 527-6000
Toll Free Tel: 1-888-794-5665
Fax: (905) 527-6660
Toll Free Fax: 1-888-794-7263
info@allredi-ca.com