

BiasiII™ Staurolite Sand Blasting Abrasive

Version Revision Date: SDS Number: Date of last issue: 06/24/2019 6.1 07/09/2019 1740596-00010 Date of first issue: 08/03/2017

SECTION 1. IDENTIFICATION

Product name : Biasill™ Staurolite Sand Blasting Abrasive

Product code : D11710971

SDS-Identcode : 130000030935

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street

Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-

773-2000); Transport emergency: +1-800-424-9300 (outside

the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Abrasive blasting

Sand blasting Foundry mould

Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Leucoxene	12173-81-8	>= 5 - < 10
Zircon	14940-68-2	>= 1 - < 5
Quartz	14808-60-7	>= 1 - < 5
Rutile (TiO2)	1317-80-2	>= 1 - < 5

Actual concentration is withheld as a trade secret



BiasiII™ Staurolite Sand Blasting Abrasive

Version Revision Date: SDS Number: Date of last issue: 06/24/2019 6.1 07/09/2019 1740596-00010 Date of first issue: 08/03/2017

SECTION 4. FIRST AID MEASURES

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.

Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

irritant effects

Protection of first-aiders : No special precautions are necessary for first aid responders.

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Not applicable

Will not burn

Unsuitable extinguishing

media

Not applicable Will not burn

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

Silicon oxides Metal oxides

Carbon oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec: :

tive equipment and emer-

Follow safe handling advice and personal protective

equipment recommendations.



BiasiII™ Staurolite Sand Blasting Abrasive

Version Revision Date: SDS Number: Date of last issue: 06/24/2019 6.1 07/09/2019 1740596-00010 Date of first issue: 08/03/2017

gency procedures

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety

practice, based on the results of the workplace exposure

assessment

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid : No special restrictions on storage with other products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Leucoxene	12173-81-8	TWA	10 mg/m³ (Titanium dioxide)	ACGIH
Zircon	14940-68-2	TWA	5 mg/m³ (Zirconium)	OSHA Z-1
		TWA	5 mg/m³ (Zirconium)	ACGIH
		STEL	10 mg/m³ (Zirconium)	ACGIH
		TWA	5 mg/m³ (Zirconium)	NIOSH REL
		ST	10 mg/m³ (Zirconium)	NIOSH REL



BiasiII™ Staurolite Sand Blasting Abrasive

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/24/2019

 6.1
 07/09/2019
 1740596-00010
 Date of first issue: 08/03/2017

Quartz	14808-60-7	TWA (Respirable dust)	0.05 mg/m³	OSHA Z-1
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (Respirable fraction)	0.025 mg/m³ (Silica)	ACGIH
		TWA (Res- pirable dust)	0.05 mg/m³ (Silica)	NIOSH REL
Rutile (TiO2)	1317-80-2	TWA	10 mg/m³ (Titanium dioxide)	ACGIH

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Quartz

Engineering measures

If using this product as an abrasive blast agent in confined areas, airborne dust levels should be controlled by physical enclosure of the abrasive blasting operation. The enclosure should be exhaust ventilated.

Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m3 - total dust, 5 mg/m3 - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m3 - respirable particles, 10 mg/m3 -

inhalable particles.

Personal protective equipment

Respiratory protection

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled

release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material : Protective gloves

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. For special



BiasiII™ Staurolite Sand Blasting Abrasive

Version Revision Date: SDS Number: Date of last issue: 06/24/2019 6.1 07/09/2019 1740596-00010 Date of first issue: 08/03/2017

applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the

product. Change gloves often!

Eye protection : Wear the following personal protective equipment:

Safety glasses

Skin and body protection : Skin should be washed after contact.

Hygiene measures : Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : solid

Color : red brown

Odor : odorless

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : 2,498 °F / 1,370 °C

Initial boiling point and boiling

range

No data available

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Will not burn

Not expected to form explosive dust-air mixtures.

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : No data available

Solubility(ies)



BiasiII™ Staurolite Sand Blasting Abrasive

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/24/2019

 6.1
 07/09/2019
 1740596-00010
 Date of first issue: 08/03/2017

Water solubility : No data available

Partition coefficient: n-

octanol/water

: Not applicable

Autoignition temperature : No data available

Decomposition temperature : The substance or mixture is not classified self-reactive.

Viscosity

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

None known.

Conditions to avoid : None known.

Incompatible materials : None.

Hazardous decomposition

products

No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Remarks: The objective of the study was to compare the lung

toxicity of a set of abrasive substitutes for silica dust (garnet, staurolite, coal slag, specular hematite, and treated sand) to that of blasting sand. Rats were intratracheally instilled with 2.5 or 10 mg/kg of the various test substances and pulmonary toxicity endpoints were measured at 4 weeks postexposure. The biomarkers included lung inflammation and cytotoxicity endpoints. In addition, the investigators measured alveolar macrophage activation. The results indicated that blasting



BiasiII™ Staurolite Sand Blasting Abrasive

Version Revision Date: SDS Number: Date of last issue: 06/24/2019 6.1 07/09/2019 1740596-00010 Date of first issue: 08/03/2017

sand produced evidence of pulmonary toxicity/inflammation and lung fibrosis. Garnet, staurolite, and treated sand exposures induced pulmonary hazard effects and inflammation that were viewed as similar to blasting sand, while coal slag instillation produced greater pulmonary damage and inflammation than blasting sand. In contrast, specular hematite did not significantly increased levels of inflammation and cytotoxicity and did not stimulate macrophage activation. [Hubbs AF et al., Toxicological Sciences volume 61: 135-143, 2001] The results of this study should be viewed as a preliminary, screeningtype pulmonary toxicity study which utilized very high, overload doses. Subsequently, the NIOSH researchers followed up on the Hubbs et al., study with another lung toxicity screening study of blasting agents ["Comparative pulmonary toxicity of blasting sand and five substitute abrasive blasting agents" -DW Porter et al., J Toxicol Environ Health A 65:1121-40, 2002]. The additional test substances included steel grit, copper slag, nickel slag, crushed glass and olivine. The authors reported that steel grit produced less lung toxicity than blasting sand or any of the other abrasive blasting substitutes

Components:

Leucoxene:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 425

Remarks: Based on data from similar materials

Zircon:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 4.3 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 436

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Quartz:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Rutile (TiO2):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 425

Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.



Biasill™ Staurolite Sand Blasting Abrasive

Version Revision Date: SDS Number: Date of last issue: 06/24/2019 6.1 07/09/2019 1740596-00010 Date of first issue: 08/03/2017

Components:

Leucoxene:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Zircon:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Rutile (TiO2):

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Information given is based on data obtained from similar sub-

stances.

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Leucoxene:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Zircon:

Species : Rabbit

Result : No eye irritation

Remarks : Based on data from similar materials

Rutile (TiO2):

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.



BiasiII™ Staurolite Sand Blasting Abrasive

Version Revision Date: SDS Number: Date of last issue: 06/24/2019 6.1 07/09/2019 1740596-00010 Date of first issue: 08/03/2017

Components:

Leucoxene:

Test Type : Buehler Test Routes of exposure : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Remarks : Based on data from similar materials

Zircon:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Remarks : Based on data from similar materials

Rutile (TiO2):

Routes of exposure : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Remarks : Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

Leucoxene:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Remarks: Based on data from similar materials

Zircon:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Rat

Application Route: inhalation (dust/mist/fume)



BiasiII™ Staurolite Sand Blasting Abrasive

Version Revision Date: SDS Number: Date of last issue: 06/24/2019 6.1 07/09/2019 1740596-00010 Date of first issue: 08/03/2017

Result: negative

Remarks: Based on data from similar materials

Rutile (TiO2):

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

Carcinogenicity

Not classified based on available information.

Components:

Zircon:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Remarks : Based on data from similar materials

Quartz:

Species : Humans

Application Route : inhalation (dust/mist/fume)

Result : positive

Remarks : IARC: (International Agency for Research on Cancer)

These substance(s) are inextricably bound in the product and

therefore do not contribute to a dust inhalation hazard.

Carcinogenicity - Assess-

ment

Positive evidence from human epidemiological studies (inhala-

tion)

Rutile (TiO2):

Carcinogenicity - Assess-

ment

Weight of evidence does not support classification as a car-

cinogen

IARC Group 1: Carcinogenic to humans

Quartz 14808-60-7

(Silica dust, crystalline)

Group 2B: Possibly carcinogenic to humans

Rutile (TiO2) 1317-80-2

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP Known to be human carcinogen

Quartz 14808-60-7

(Silica, Crystalline (Respirable Size))

Reproductive toxicity

Not classified based on available information.



BiasiII™ Staurolite Sand Blasting Abrasive

Version Revision Date: SDS Number: Date of last issue: 06/24/2019 6.1 07/09/2019 1740596-00010 Date of first issue: 08/03/2017

Components:

Zircon:

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Rutile (TiO2):

Reproductive toxicity - As-

sessment

Weight of evidence does not support classification for

reproductive toxicity

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Components:

Zircon:

Routes of exposure : inhalation (dust/mist/fume)

Assessment : No significant health effects observed in animals at concentra-

tions of 0.2 mg/l/6h/d or less.

Quartz:

Routes of exposure : inhalation (dust/mist/fume)

Target Organs : Lungs

Assessment : Shown to produce significant health effects in animals at con-

centrations of 0.02 mg/l/6h/d or less.

Rutile (TiO2):

Assessment : No significant health effects observed in animals at concentra-

tions of 100 mg/kg bw or less.

Repeated dose toxicity

Components:

Zircon:

Species : Rat

NOAEL : $> 100.8 \text{ mg/m}^3$

Application Route : inhalation (dust/mist/fume)

Exposure time : 30 Days

Remarks : Based on data from similar materials

Quartz:

Species : Humans LOAEL : 0.053 mg/m³

Application Route : inhalation (dust/mist/fume)

Remarks : These substance(s) are inextricably bound in the product and



BiasiII™ Staurolite Sand Blasting Abrasive

Version Revision Date: SDS Number: Date of last issue: 06/24/2019 6.1 07/09/2019 1740596-00010 Date of first issue: 08/03/2017

therefore do not contribute to a dust inhalation hazard.

Rutile (TiO2):

Species : Rat

NOAEL : 24,000 mg/kg LOAEL : > 24,000 mg/kg

Application Route : Ingestion Exposure time : 28 d

Remarks : No significant adverse effects were reported

Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Leucoxene:

Toxicity to fish : LC50 (Cyprinodon variegatus (sheepshead minnow)): > 100

mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EC50 (Skeletonema costatum (marine diatom)): > 100 mg/l

Exposure time: 72 h Method: ISO 10253

Remarks: Based on data from similar materials

NOEC (Skeletonema costatum (marine diatom)): > 1 mg/l

Exposure time: 72 h Method: ISO 10253

Remarks: Based on data from similar materials

Zircon:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Remarks: Based on data from similar materials

Toxicity to algae/aquatic : NOEC (Chlorella vulgaris (Fresh water algae)): > 200 mg/l



BiasiII™ Staurolite Sand Blasting Abrasive

Version Revision Date: SDS Number: Date of last issue: 06/24/2019 6.1 07/09/2019 1740596-00010 Date of first issue: 08/03/2017

plants Exposure time: 15 d

Remarks: Based on data from similar materials

Quartz:

Ecotoxicology Assessment

Acute aquatic toxicity : No toxicity at the limit of solubility.

Chronic aquatic toxicity : No toxicity at the limit of solubility.

Rutile (TiO2):

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

ErC50 (algae): > 10,000 mg/l

Exposure time: 72 h

Remarks: Based on data from similar materials

NOEC (algae): 5,600 mg/l Exposure time: 72 h

Remarks: Based on data from similar materials

Persistence and degradability

No data available

Bioaccumulative potential

Components:

Rutile (TiO2):

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Based on data from similar materials

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.



BiasiII™ Staurolite Sand Blasting Abrasive

Version Revision Date: SDS Number: Date of last issue: 06/24/2019 6.1 07/09/2019 1740596-00010 Date of first issue: 08/03/2017

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

 Staurolite
 12182-56-8

 Tourmaline
 1317-93-7

 Leucoxene
 12173-81-8

 Quartz
 14808-60-7

 Rutile (TiO2)
 1317-80-2

California Prop. 65

WARNING: This product can expose you to chemicals including Quartz, Quartz, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.



BiasiII™ Staurolite Sand Blasting Abrasive

Version Revision Date: SDS Number: Date of last issue: 06/24/2019 6.1 07/09/2019 1740596-00010 Date of first issue: 08/03/2017

California List of Hazardous Substances

Zircon 14940-68-2

California Permissible Exposure Limits for Chemical Contaminants

Zircon 14940-68-2 Quartz 14808-60-7


California Regulated Carcinogens

Quartz 14808-60-7

SECTION 16. OTHER INFORMATION


Further information

NFPA 704:



Special hazard.

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Biasill™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

The stated hazards of this material are based on non-inhalable particles that are the bulk fraction of the delivered product. However, if during handling or use the particles are broken down to the inhalable or respirable size range, the dusts may be harmful to the respiratory system. Inhalable quartz is an IARC Category 1 carcinogen and applicable exposure limits should be referenced. Staurolite Products contain trace quantities of naturally occurring radioactive uranium and thorium = 200 ppm total U + Th or 0.02 % w/w.

For a total dust with aerodynamic diameter of 1 um, the calculated reference dust level is 6.9 mg/m3. For a total dust with aerodynamic diameter of 5 um, the calculated reference dust level is 10.8 mg/m3. For a total dust with aerodynamic diameter of 10 um, the calculated reference dust level is 15.9 mg/m3.

Full text of other abbreviations



BiasiII™ Staurolite Sand Blasting Abrasive

Version Revision Date: SDS Number: Date of last issue: 06/24/2019 6.1 07/09/2019 1740596-00010 Date of first issue: 08/03/2017

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NTP - National Toxicology Program: NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG -United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 07/09/2019



BiasilI™ Staurolite Sand Blasting Abrasive

Version Revision Date: SDS Number: Date of last issue: 06/24/2019 6.1 07/09/2019 1740596-00010 Date of first issue: 08/03/2017

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8