

BINKS MX SERIES

Airless Spray Outfits

FLUID HANDLING



Heavy Duty Pumping Power
for Protective Coating and
Corrosion Control Applications



Binks MX Series Airless Spray Outfits

Binks MX Pumps are a completely new design in air operated pump technology utilizing a patented magnetic detents to provide fast changeover with virtually no pulsation. The result is paint delivery with less pulsation for a more consistent finish.

The MX pumps are available in ratios of 35:1, 42:1, 60:1, 70:1 with output of 3.0 GPM or 3.5 GPM. The MX pistons are Ceramic coated which is the most durable surface available for resisting wear to highly abrasive materials.

TYPICAL MATERIALS & APPLICATIONS

- Solvent coatings
- Waterborne coatings
- Zinc rich primers and paints
- Cold tar epoxies
- High solids epoxies and urethanes
- Plural component enamels and polyurethanes

And many others



STEEL FABRICATIONS AND STRUCTURES



PIPE AND STORAGE TANKS




MARINE AND SHIP BUILDING



LARGE VEHICLES, TRAILERS, RAILCARS AND CHASSIS MANUFACTURERS

BINKS MX SERIES FEATURES

FEATURE	STANDARD	COMPETITION*
LONG LASTING CERAMIC COATED PISTON RODS Resists wear from highly abrasive fluids and lasts up to 3X longer than hard chrome	✓	NO
EXTENDED PACKING LIFE Spring loaded fixed packings last up to 3X longer than the competition	✓	NO
LOW/NO ICE Operate 2.5X longer than the competition	✓	NO
PATENTED AIR VALVE TECHNOLOGY Enables pump to change over quickly without pulsing	✓	NO
LUBRICANT FREE AIR MOTOR AND VALVE DESIGN Reduces Maintenance and simplifies operation	✓	NO
5 YEAR LIMITED WARRANTY 	✓	NO
LOW NOISE < 78 dBA at 80 psi air inlet pressure	✓	NO



MX HD pumps are designed to operate at longer intervals in between repairs and reduce the overall cost of ownership

* Comparison to major airless pump manufacturer



Shown: Binks MX Cart-Mount Outfit with Airless 75 spray gun, 25' airless hose, 5' whip hose and 5 gal. siphon kit.

Air Controls included for pump and/or air assist spray gun applications

Patented Anti-stall Magnetic Detent Technology with quick exhaust valves feature low to no ice operation and uninterrupted production

Air Motor Silencer for quiet operation

Durable Hose Bracket for convenient storage

Carbon or Stainless Steel Housing with Ceramic Coated Step Rod Design reduces friction in the pump rod movement and is proven tough to increase packing life

Manual Fluid Pressure Relief Valve for easy operation

Flat Free Tires require no maintenance

Large 1 1/2" "Knock Off" Fluid Inlet for faster pump assembly and disassembly in the field

Mounting Setups:

- Bare Pump (no mount provided)
- Cart-Mount (shown above)
- Wall-Mount (not shown)

BINKS MX SERIES PERFORMANCE DATA

BINKS MX SERIES PUMP	MX3042	MX3560	MX3070
Ratio	42:1	60:1	70:1
Max. Inlet Pressure	101.5 psi [7 bar]	116 psi [8 bar]	101.5 psi [7 bar]
Flow Rate @ 60 cycles (continuous)	3.0 gpm [11.4 l/m]	3.5 gpm [13.2 l/m]	3.0 gpm [11.4 l/m]
Volume Cycle	6.4 oz [190 CC]	7.4 oz [220 CC]	6.4 oz [190 CC]
Max Fluid Pressure	4,263 psi [294 bar]	6,960 psi [480 bar]	7,105 psi [490 bar]
Cylinder Diameter	7.87 in [200mm]	10 in [260 mm]	10 in [260 mm]
Piston Stroke	5 in [127mm]	5 in [127mm]	5 in [127mm]

MX SERIES ACCESSORIES, SPARES AND KITS

ACCESSORIES AND SPARES	MX3042	MX3536	MX3560	MX3070
Airless 75 Gun with Stainless Steel Fluid Tube		0811-7500-1		
Airless 75 Gun Direct Connect		0811-7500-2		
Airless 75 Gun Direct Connect large passage		0811-7500-3		
Cart Assembly	41-28280-200		41-28280-MX	
Wall Bracket Assembly	104116		104095	
Silencer		192509		
Binks Micro-Swivel 1/4" NPS (F) to 1/4" NPS (M) (7,550 psi)		72-2332		
Binks Micro-Swivel 1/4" NPS (F) to 3/8" NPS (M) (7,550 psi)		72-2333		

HIGH PRESSURE FILTER ELEMENTS

30 Mesh	0114-014917
50 Mesh	0114-014886
70 Mesh	0114-014884
100 Mesh	0114-014883

AIR MOTOR SPARES KIT

	MX3042	MX3536	MX3560	MX3070
Seal Kit	250703		250645	
Cylinder Seal Kit	250702		250648	
Hardware Kit	250701		250650	
Air Valve Repair Kit		250649		
Exhaust Seal Kit		250651		

FLUID SECTION REPAIR KIT

	MX3042	MX3536	MX3560	MX3070
Fluid Section Rebuild Kit	250665	250661	250661	250665
Fluid Section Seal Kit	250663	250659	250659	250663

MX SERIES ORDERING INFORMATION

MX3560 60:1 pump carbon steel lower fluid section with PTFE/UHMW packings sold with a 100 mesh filter, 5-gal siphon kit, Airless 7500 gun w/fluid tube no tip, 50' airless hose with 5' whip hose.

*Specify tip separately when ordering



MX 35 60 PU- C A C 1 S 1 2

A OUTPUT

30 = 3.0 GPM
35 = 3.5 GPM

B RATIO

36 = 36:1
42 = 42:1
60 = 60:1
70 = 70:1

C MATERIAL

C = Carbon Steel
S = Stainless Steel

D MOUNTING

C = Cart
W = Wall

E FILTER

1 = 100 Mesh
3 = 30 Mesh
5 = 50 Mesh
7 = 70 Mesh

F SIPHON

O = None
S = 5 Gallon
T = 55 Gallon

G GUN

O = No Gun
1 = Airless 75 Fluid Tube 0811-7500-1
5 = Airless 75 Large Passage 0811-7500-3

H HOSE

O = None
2 = 25 Feet
5 = 50 Feet



BINKS MX SERIES 5-YEAR WARRANTY

Binks® warrants to the original end-use purchaser that the Binks branded products "MX" shall not fail under normal use and service due to a defect in material or workmanship within five (5) years from the date of shipment from Binks. Does not include normal wear and tear parts.

For further technical information please refer to the Binks MX Series Service Bulletins, 77-2960 and 77-2963.



SOLUTIONS FOR YOUR WORLD

World Class Manufacturers of: | Process Controls | Curing & Conveying
Electrostatics | Fluid Handling | Powder Coating | Atomization

Carlisle Fluid Technologies US
16430 N. Scottsdale Road, Suite 450
Scottsdale, AZ 85254

Tel: 1-800-992-4657
Fax: 877-790-6965
Email: ghcustserv@carlisleft.com