

83909TP3

9' DuraTech® Leading Edge Personal SRL with Steel Rebar Hooks

Features :

- Proprietary aluminum alloy dorsal connector provides simplified push button attachment
- Exclusive energy absorber design with nylon fused EVA cover limits user back discomfort.
- Constant-force main spring produces smooth lifeline payout and retraction
- Calibrated pawl locking system delivers ideal walking speed without nuisance lock-up
- Lightweight and impact resistant nylon polymer housing provides greater durability
- Versatile anchorage range from overhead up to 5' below user's dorsal D-ring
- 3/16" galvanized steel cable lifelines with plated alloy steel rebar hooks
- Rebar hooks feature transverse load rated gates
- Complies with ANSI Z359.14-2014



Material Specifications	
Cable	3/16" galvanized steel; 3,400 lb min. static strength
Energy Absorber	Polyester tear-away
Anchorage Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
Dorsal Connector	Aluminum alloy; 3,000 lb min.

Performance Specifications	
Static Strength	3,000 lb min.
ANSI SRL Class	Class B
Avg. Arrest Force	900 lb
Max. Arrest Force	1,800 lb
Max. Arrest Distance	54"
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 310 lb max.

Compliant With:	
OSHA	1926.502 and 1910.66
ANSI	Z359.14-2014

