

Cut, Impact, Puncture, and Abrasion Resistant Nitrile Double-Coated Gloves

DESCRIPTION

This seamless, 13-gauge Tuffalene® UHMWPE glove offers excellent cut resistance, TPU impact resistance, and dexterity. The shell is enhanced by a double-dipped Mach Finish nitrile dipped palm for superior wet/dry grip and abrasion resistance.

INDUSTRY

Glass Handling	Construction
Bottle Handling	Metal Fabrication
Automotive Industry	Metal Stamping
Aerospace Industry	Oil and Gas



ITEM CIA617V

SIZES 7(S)-11(2XL)

FEATURES

- Soft, flexible, TPU impact protection over the fingers and metacarpal bones provides tough protection
- Reinforced thumb crotch increases abrasion resistance in vulnerable area
- Padded palm increases comfort and dampens vibration
- Double-dipped Mach Finish nitrile offers excellent grip in wet and oily conditions and prevents liquids from saturating gloves
- 13-gauge Tuffalene® shell offers cut resistance
- Knit wrist with hook-and-loop closure allows users a secure and comfortable fit
- ANSI Cut Level A5
- ASTM F2992-15 Results = 2,425 grams
- ANSI Puncture Level 3
- ANSI Puncture Results: 73 Newtons
- EN 388 Levels: 4X43D
- ANSI/ISEA 138 Impact Level (Overall): 1

SPECIFICATIONS

SHELL	SHELL COLOR	GAUGE	COATING	COATING COLOR	COATING TYPE	FINISH	IMPACT PROTECTION
Tuffalene® UHMWPE	Blue/White	13-Gauge	Double Nitrile	Black	Palm	Mach Finish	TPU
REINFORCED AREA	CUFF	ANSI CUT	ANSI PUNCTURE	EN 388 LEVELS	ASTM F2992-15 RESULTS	PUNCTURE RESULTS	
Thumb Crotch	Knit Wrist with Hook-and-Loop	Level A5	Level 3	4X43D	2,425 Grams	73 Newtons	

PACKAGING

	QUANTITY	7(S)	8(M)	9(L)	10(XL)	11(2XL)
PAIR UPC	1	NA	NA	NA	NA	NA
INNER PACK UPC	12/PACK	810292029951	816679012080	816679012073	816679012097	816679012066
CASE GTIN	6 PK/CASE	10810292029958	10816679012087	10816679012070	10816679012094	10816679012063
CASE WEIGHT (IN POUNDS)		33	34	34	34.2	38
OVERCAST COLOR		Red	Green	Brown	Black	Light Blue